


Intermediate Dynamics

Kinematics of a Point Moving on a Rigid Body

The kinematic analysis is now extended to include systems where interconnected bodies can *rotate* and *translate* relative to each other. In these cases, there is a need to describe the kinematics of points that are moving on (relative to) a rotating body. To analyze this motion, consider the figure shown at the right. Here,



R : a fixed reference frame

B : a moving rigid body

P : a point *moving* on B

\hat{P} : a point *fixed* on B that *coincides* with P at this instant of time

The *velocity* and *acceleration* of P can be written as

$$\boxed{{}^R \underline{v}_P = {}^R \underline{v}_{\hat{P}} + {}^B \underline{v}_P}$$

$$\boxed{{}^R \underline{a}_P = {}^R \underline{a}_{\hat{P}} + {}^B \underline{a}_P + 2\left({}^R \underline{\omega}_B \times {}^B \underline{v}_P\right)}$$

Here, each of the terms are defined as follows.

${}^B \underline{v}_P, {}^B \underline{a}_P$: velocity and acceleration of P on B , assuming that B is fixed

${}^R \underline{v}_{\hat{P}}, {}^R \underline{a}_{\hat{P}}$: velocity and acceleration of \hat{P} in R (recall that \hat{P} is fixed on B)

$2\left({}^R \underline{\omega}_B \times {}^B \underline{v}_P\right)$: Coriolis acceleration of P

Note: The *velocity* and *acceleration* of \hat{P} can be determined using the formulae for points fixed on rigid bodies. See notes on “Relative Kinematics of Two Points Fixed on a Rigid Body”.

Derivation

The results shown above can easily be shown by using “the derivative rule”. Consider the rigid body shown in the diagram at the right. Here,


R : fixed reference frame

B : moving rigid body

P : point **moving** on B

\hat{P} : point **fixed** on B that *coincides* with P

Q : point **fixed** on B



The **velocity** of P can be found by **differentiating** its position vector as follows.

$$\begin{aligned} {}^R \underline{v}_P &= \frac{{}^R d}{dt} \underline{p} = \frac{{}^R d}{dt} (\underline{q} + \underline{r}) \\ &= \frac{{}^R dq}{dt} + \frac{{}^R dr}{dt} \\ &= {}^R \underline{v}_Q + \frac{{}^B dr}{dt} + ({}^R \underline{\omega}_B \times \underline{r}) \\ &= {}^R \underline{v}_Q + {}^B \underline{v}_P + ({}^R \underline{\omega}_B \times \underline{r}) \end{aligned}$$

Now, letting $\underline{r} \rightarrow \underline{0}$ (that is, letting Q be \hat{P}) the desired result is obtained. The **acceleration** of P can be found by **differentiating** the expression for its velocity.

$$\begin{aligned} {}^R \underline{a}_P &= \frac{{}^R d}{dt} ({}^R \underline{v}_Q + {}^B \underline{v}_P + ({}^R \underline{\omega}_B \times \underline{r})) \\ &= \frac{{}^R d}{dt} ({}^R \underline{v}_Q) + \left\{ \frac{{}^R d}{dt} ({}^B \underline{v}_P) \right\} + \left\{ \frac{{}^R d}{dt} ({}^R \underline{\omega}_B \times \underline{r}) \right\} \\ &= {}^R \underline{a}_Q + \left\{ \frac{{}^B d}{dt} ({}^B \underline{v}_P) + ({}^R \underline{\omega}_B \times {}^B \underline{v}_P) \right\} + \left\{ ({}^R \underline{\alpha}_B \times \underline{r}) + {}^R \underline{\omega}_B \times \left(\frac{{}^B dr}{dt} + ({}^R \underline{\omega}_B \times \underline{r}) \right) \right\} \\ &= {}^R \underline{a}_Q + \left\{ {}^B \underline{a}_P + ({}^R \underline{\omega}_B \times {}^B \underline{v}_P) \right\} + \left\{ ({}^R \underline{\alpha}_B \times \underline{r}) + ({}^R \underline{\omega}_B \times {}^B \underline{v}_P) + {}^R \underline{\omega}_B \times ({}^R \underline{\omega}_B \times \underline{r}) \right\} \end{aligned}$$

Now, letting $\underline{r} \rightarrow \underline{0}$ (that is, letting Q be \hat{P}) the desired result is obtained.